



YATLANT  
**BOST**



YATLANT  
**SETE**



YATLANT  
**OITO**

## Yatlant

Design and manufacturing  
YATLANT  
T. (+34) 617 822 938  
[www.yatlant.eu](http://www.yatlant.eu)  
[info@yatlant.eu](mailto:info@yatlant.eu)

Polígono Industrial  
Bergondo.  
Parcela G-8  
15165 Bergondo - A Coruña  
España

The information contained in this catalog is for informational purposes only. To specify and/or clarify some or all of the information, as well as to formalize a specific order, or for any other matter of interest, please contact YATLANT or one of its Official Representatives so that they can inform you in detail about the special features, original equipment, options, price, specifications, campaigns, promotions, availability of units, delivery times, manufacturing periods, etc., of the models referenced here.



DISCOVER OUR MODELS  
**EXPERIENCES  
WITHOUT  
LIMITS**

DESIGNED TO ENJOY THE SEA AND  
THE WIND.  
HIGH QUALITY FINISHES AND  
VERSATILE DESIGN THAT ADAPTS  
PERFECTLY TO ANY SAILING  
CONDITION





YATLANT  
**BOST**

OVERALL LENGTH	5.2 m
HULL LENGTH	5.2 m
BEAM	2.2 m
DRAFT	1.4 m
DISPLACEMENT	325 kg
BALLAST	150 kg
SAIL AREA MAIN	11 m <sup>2</sup>
JIB	5 m <sup>2</sup>

**HULL.** Isophtalic Gel-coat NPG. Vinylester infusion laminate. Structural infusion counter-moulds glued and laminated to the hull. Integrated bowsprit.

**DECK.** Isophtalic gel-coat NPG. Infusion laminate with isophtalic polyester resin with PVC core density of 75 kg/m3 and high density in reinforcements. Non slip finish.

**FEATURES**

**Rudders.** Vinylester infusion laminates and E-fibreglass. Keel. Lead, Naca profile with 150 kg bulb.

**Rig.** Sloop 9.5/10, 1 set of 25° swept spreaders. Aluminium boom.

Rigid vang.

**Standing rigging** in 1x19 mm wire.

**Deck hardware.** Mainsheet tackle. 6 mast foot blocks. Jammers and cleats.

**Running Rigging.** Main and genoa halyards in Dyneema. Mainsheet. Jib sheet. Vang tackle. Outhaul.

**Safety. Unsinkable.**

YATLANT  
**SETE**

OVERALL LENGTH	7 m
HULL LENGTH	6.5 m
BEAM	3 m
DRAFT	1,75 m
DISPLACEMENT	980 kg
BALLAST	450 kg
SAIL AREA MAIN	22 m <sup>2</sup>
JIB	12 m <sup>2</sup>
CODE 5	32 m <sup>2</sup>
ASYMETRIC SPINNAKER	55 m <sup>2</sup>

**HULL.** Isophtalic Gel-coat NPG. Vinylester infusion laminate. Structural infusion counter-moulds glued and laminated to the hull. Composite divided bulkheads. Integrated bowsprit. Epoxy treatment under the waterline.

**DECK.** Isophtalic gel-coat NPG. Infusion laminate with isophtalic polyester resin with PVC core density of 75 kg/m3 and high density in reinforcements. Non slip finish. Anchor well. Port and starboard windows and hatch in polycarbonate.

**INTERIOR.** Interior height 1.4 m. Structural infusion counter-moulds and composite bulkheads. Double cabin at bow. Central saloon, locker at starboard, cabin at port.

**FEATURES**

**Rudders.** Vinylester infusion laminates and E-fibreglass. Tiller in composite and long tiller extension.

**Keel.** Lead, Naca profile with 450 kg bulb.

**Rig.** Sloop 9.5/10, 1 set of 25° swept spreaders. Keel stepped mast. Aluminium boom. Rigid vang.

**Standing rigging** in 1x19 mm wire of Ø 4 and 5 mm.

**Deck hardware.** Mainsheet track with ball bearings. 6 mast foot blocks. Jammers and cleats. 2 ST winches size 12 for sheets. 2 winches size 10 for halyards.

**Running Rigging.** Main and genoa halyards in Dyneema. Spinnaker halyard. Vang tackle. Outhaul tackke. Reef 1. Mainsheet. Jib sheet. Vang tackle. Outhaul.

**Safety.** Compass. Manual bilge pump. Bow pulpits. Stern pulpit. Four stanchions. Lifeline.

YATLANT  
**OITO**

OVERALL LENGTH	8 mt
HULL LENGTH	7.5 m
BEAM	3 m
DRAFT	1,8 m
DISPLACEMENT	1.180 kg
BALLAST	550 kg
SAIL AREA MAIN	25 m <sup>2</sup>
JIB	13 m <sup>2</sup>
CODE 5	35 m <sup>2</sup>
ASYMETRIC SPINNAKER	60 m <sup>2</sup>

**HULL.** Isophtalic Gel-coat NPG. Vinylester infusion laminate. Structural infusion counter-moulds glued and laminated to the hull. Composite divided bulkheads. Integrated bowsprit. Epoxy treatment under the waterline.

**DECK.** Isophtalic gel-coat NPG. Infusion laminate with isophtalic polyester resin with PVC core density of 75 kg/m3 and high density in reinforcements. Non slip finish. Anchor well. Port and starboard windows and hatch in polycarbonate.

**INTERIOR.** Interior height 1.4 m. Structural infusion counter-moulds and composite bulkheads. Double cabin at bow. Central saloon, locker at starboard, cabin at port.

**FEATURES**

**Rudders.** Vinylester infusion laminates and E-fibreglass. Tiller in composite and long tiller extension.

**Keel.** Lead, Naca profile with 450 kg bulb.

**Rig.** Sloop 9.5/10, 1 set of 25° swept spreaders. Keel stepped mast. Aluminium boom. Rigid vang.

**Standing rigging** in 1x19 mm wire of Ø 4 and 5 mm.

**Deck hardware.** Mainsheet track with ball bearings. 6 mast foot blocks. Jammers and cleats. 2 ST winches size 12 for sheets. 2 winches size 10 for halyards.

**Running Rigging.** Main and genoa halyards in Dyneema. Spinnaker halyard. Vang tackle. Outhaul tackke. Reef 1. Mainsheet. Jib sheet. Vang tackle. Outhaul.

**Safety.** Compass. Manual bilge pump. Bow and stern pulpits. Four stanchions. Lifeline.